



### Main

Range	Clipsal Iconic
Product or component type	Switch mechanism
Device presentation	Mechanism
Provided equipment	Switch Rocker dolly
Device application	Lighting
Fixing mode	Locking bar
Colour tint	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	10 AX - 250 V AC, 50 Hz

### Complementary

Switch function	3 positions
Control type	Rocker
Actuator	Rocker
Product destination	Sensor
Marking	ON-OFF-ON
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	0...60 °C
Motor M-rating AS3133	M40
Load type	Inductive Inductive Light Fluorescent lamp
Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm <sup>2</sup> (stranded) 1.5 mm <sup>2</sup> (flexible) 1.5 mm <sup>2</sup> (rigid)
Wire stripping length	10 mm
Material	Housing : PC (polycarbonate) Housing : PA66 Dolly : PC (polycarbonate) Dolly : ABS (acrylonitrile butadiene-styrene)
Height	23 mm
Width	23 mm
Depth	32 mm
Product weight	0.016 kg

### Environment

product certifications	RCM
------------------------	-----

**Offer Sustainability**

---

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold

---