

MERCURY BLACK

LOW ILLUMINATION EMERGENCY EXIT SIGN



FEATURES

- Fully compliant (AS/NZS 2293)
- Premium Lithium batteries (LiFePO4) and smart charger
- Viewing distance 24M
- Low illumination
- Single and double sided decal
- Rod / surface / suspended or wall mounted



WIRELESS UPGRADE:

Automatically test and sync data to the Cloud



DALI CERTIFIED:

Connect to a DALI system for DALI testing



SELF TEST:

Commission the product to perform its own tests



SINGLE POINT UNIT:

Ektor products work as SPUs out of the box

Ph: + 612 9502 1161 Fax: + 612 9502 1154 a brand of | evolt Email: sales@evolt.com.au ektor.com.au




ORDERING INFORMATION				
CODE	PRODUCT CODE	DESCRIPTION	PRODUCT NUMBER	CARTON QTY
03136	EV-MERCURY-B	Mercury Emergency Exit Black	9336462031360	4

OPERATIONAL INI	FORMATION				
GENERAL				BATTERY	
Voltage Frequency Ambient temp.	220~240V 50Hz 0 - 40°C		IP20 (IP65 Weatherproof case) Rod / surface / suspended or wall mounted	Battery type Battery code	LiFePO4 01300
Class Wiring Viewing distance	2 Terminal block 24M	Duration	1/2/3/4 hours (dependant on jumpers)	Charger type Charging time Charging operation	Smart charge 16 hours Multi state

EMERGENCY PERFORMANCE						
HOUR	1	2	3	4	8	CB
Lamp power (W)	1.05	1.05	1.05	0.53	-	1.05

TOTAL POWER CONSUMPTION (TPC)				
MAINTAIN	NED MODE	NON-MAINTAINED MODE		
Max.	Avg.	Max.	Avg.	
4.5 W	2.5 W	3 W	0.25 W	



ACCESSORIES				
CODE	ORDER CODE	DESCRIPTION		
01996	EV-MERCURY-DP-B	Mercury decal pack black		
03922	EV-MERCURY-CASE-WP	Mercury weatherproof case		
01211	EV-MERCURY-B-INV	Mercury inverter black		
01300	EV-1000MAH-6.4V-LIFEP04	Battery, side by side 1000mAh 6.4V, 2 Cell LiFePO4		
06118	ZC-WIFI	Zencontrol - Wi-Fi daughterboard compatible with Ektor devices		
05304	ZC-ECM-DALI	Zencontrol - Easy Commissioning Module - DALI		

Datasheet is subject to change without notice Last updated: **15. March 2017_V1.4**



Please view our website for **full datasheet**