



Representative Photo Only  
(actual product may vary based on configuration selections)

AUX CONTACT MODULE 1N/O+1N/C RIGHT MOUNT

- UL 1077, for supplementary protection
- Current limiting type MCB with B, C, and D-trip curves
- 0.5 - 63A current ratings
- 40°C calibration temperature (UL / CSA) eliminates the need to derate for 508A industrial control panel installations

**SPECIFICATIONS**

|                                                |                                     |
|------------------------------------------------|-------------------------------------|
| Product Series                                 | Bul. 1492-SP                        |
| Component Type Power Distribution & Protection | Auxiliary Contact                   |
| Rated Frequency                                | 50 / 60 Hz                          |
| Un, Nominal Operational Voltage, AC            | 230 V AC                            |
| Ie, Rated Operational Current, AC-14, 230V     | 2 A@230V                            |
| Ie, Rated Operational Current, AC-14, 400V     | 1 A@400V                            |
| Contact Configuration                          | 1 NO + 1 NC EB 1st Contact          |
| Height                                         | 74 mm                               |
| Width                                          | 85 mm                               |
| Depth                                          | 8.8 mm                              |
| Mechanical Service Life                        | 20000 cycles                        |
| Operating Temperature, Min                     | -25 °C min                          |
| Operating Temperature, Max                     | 55 °C max                           |
| Storage Temperature, Min                       | -40 °C min                          |
| Storage Temperature, Max                       | 70 °C max                           |
| Relative Humidity, Min                         | 90 %RH                              |
| Relative Humidity, Max                         | 96 %RH                              |
| Humidity Type                                  | Non-condensing                      |
| Shock Acceleration (Max.)                      | 25 g                                |
| Shock Duration (Max.)                          | 13 ms                               |
| Shock Rating                                   | IEC 60068-2-27                      |
| Vibration Acceleration (Max.)                  | 5 m/s <sup>2</sup>                  |
| Vibration Frequency, Operational (Max.)        | 150 Hz                              |
| Vibration Rating                               | IEC 60068-2-6                       |
| Standards Compliance                           | UL 1077<br>EN 60947-2<br>GB 14048-2 |

# Catalogue No: **189-AR11**

## MCB ACC AUX CONTACT 1NO+1NC RIGHT MOUNT

Power Distribution and Protection > Circuit Breakers > Miniature Circuit Breakers and Earth Leakage Protection (RCDs and RCBOs) > Allen-Bradley Miniature Circuit Breakers (Bulletin 1492-SPM, 1489-M) > Bulletin 1492-SPM Circuit Breakers > Accessories



### Certifications

UL  
CSA  
CE  
CCC  
VDE  
RoHS

### REFERENCES

IECEx Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -