



Main

| | |
|---------------------------|---|
| Range of product | Thorsman |
| Product or component type | Cavity fixing |
| Device short name | TPD-VS |
| Provided equipment | Without screw |
| Device application | 9 mm lightweight installation in plasterboard |
| Colour tint | White |
| Quantity per set | Set of 100 |

Complementary

| | |
|-------------------------|---|
| Mounting support | Wall mounted |
| Material | PA (polyamide) Glass fibre reinforced |
| Practical load capacity | 0.5 kN pull-out load : 13 mm board 0.19 kN shear : 13 mm board |
| Thickness | 0...12 mm fixture |
| Diameter | 13 mm |
| Length | 37 mm |
| Product weight | 0.177 kg |

Environment

| | |
|---------------------------------------|-------------|
| ambient air temperature for operation | -40...80 °C |
|---------------------------------------|-------------|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | 7315881220014 |
| RoHS (date code: YYWW) | Compliant - since 1002 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | 7315881220014 |
| Product end of life instructions | 7315881220014 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.