

A9MEM3465

iEM3465 energy meter - BACnet - 1 DI - 1 DO - multi-tariff - LVCT



Main

Range	Acti 9
Product name	Acti 9 iEM3000
Device short name	IEM3465
Product or component type	Energy meter

Complementary

Poles description	1P + N 3P 3P + N
Type of measurement	Voltage Current Active and reactive power Active and reactive energy
Metering type	Active, reactive, apparent energy (signed, four quadrant)
Device application	Sub billing Multi-tariff Partial meter
Accuracy class	Active energy : class 0.5S according to IEC 62053-22 Active energy : class 0.5S according to ANSI C12.20
Analogue input type	Split core current transducer 0.333 V or 1 V
Rated voltage	100...277 V +/- 20% 173...480 V +/- 20 %
Network frequency	50 Hz 60 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	1 mA...32767 A
Maximum value measured	99999999 MWh 99999999.9 kWh
Information displayed	4 tariff
Communication port protocol	BACnet 9.6, 19.2, 38.4, 57.6, 76.8 kbauds
Communication port support	Screw terminal block : RS485
Local signalling	Power ON : indicator light (green) Accuracy checking : flashing LED (yellow) Overload : alarm
Number of inputs	1 digital 0...5 V/11...40 V 24 V DC
Number of outputs	1 digital (static)
Output voltage	5...40 V DC < 50 mA
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Current circuit : screw terminals 6 mm ² Voltage circuit : screw terminals 2.5 mm ² Input/output circuit : screw terminals 1.5 mm ² Communication : screw terminals 2.5 mm ²
Tightening torque	Input/output circuit : 0.5 N.m Philips Voltage circuit : 0.5 N.m Philips Current circuit : 0.8 N.m pozidriv

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Communication : 0.5 N.m Philips

Wire stripping length	6 mm input/output circuit 8 mm voltage circuit 8 mm current circuit 7 mm communication
Standards	IEC 61036 IEC 61557-12 IEC 62053-21 IEC 62053-23 IEC 61010 UL 61010-1
Product certifications	UL EAC (sub-meter) CE - IEC 61010 (safety) CE - IEC 61326-1 (EMC) CULus - ANSI C12.20 (sub-meter) RCM - NMI M 6-1 (sub-meter) CE - EN 61557-12 (power monitor) CULus - UL 61010 (safety)

Environment

IP degree of protection	IP40 (front panel) conforming to IEC 60529 IP20 (body) conforming to IEC 60529
IK degree of protection	IK08
pollution degree	2
relative humidity	5...95 % at 36 °C
ambient air temperature for operation	-25...70 °C (IEC) -25...70 °C (MID) -25...70 °C (NMI)
ambient air temperature for storage	-40...85 °C
operating altitude	< 3000 m
colour	White
9 mm pitches	10
width	90 mm
height	87 mm
depth	69 mm

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1530 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available