



Main

Range	PowerLogic
Product or component type	USB interface
Number of channels	1
Bandwidth	2405...2480 MHz FCC conforming to IEEE 802.15.4 2405...2480 MHz ETSI conforming to IEEE 802.15.4
Transmission rate	12 Mbps

Complementary

Communication port protocol	USB
Communication network type	ZigBee
[Us] rated supply voltage	5 V DC
Current consumption	TX (transmission) <= 100 mA for 5 V DC RX (reception) <= 70 mA for 5 V DC
Height	19 mm
Depth	9 mm

Environment

ambient air temperature for operation	-25...85 °C
ambient air temperature for storage	-40...85 °C
standards	IEEE 802.15.4
width	38 mm

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.