Product datasheet
Characteristics

LVCT01604S

LV CT 1600 A - 0.333 V output - split core CT - 62 mm x 201 mm

Main

Range	PowerLogic
Device short name	LVCT
Product or component type	Current transformer
Output voltage	0.333 V
Electrical connection	Cable 1.8 m AWG 18 600 V
Product destination	BCPMSC BCPM Enercept EM3500 IEM3000
Accessory / separate part category	Measurement accessory
Current transformer type	Split core balance
[In] rated current	1600 A
Network frequency	50/60 Hz

Complementary

Range compatibility	Powerlogic EM3502 Powerlogic EM3555 Powerlogic BCPMA Powerlogic BCPME Powerlogic EM3561 Powerlogic EM4235 Powerlogic EM4236 Acti 9 iEM3455 Powerlogic BCPMB Powerlogic BCPMSCA Powerlogic BCPMSCB Powerlogic BCPMSCE Powerlogic EM3550 Powerlogic EM3560 Acti 9 iEM3465
Measurement accuracy	1 % 10...100 %

Environment

relative humidity	95 %
ambient air temperature for operation	-15...60 °C
ambient air temperature for storage	-40...70 °C
width	62 mm internal 151 mm external
depth	30 mm
height	139 mm internal 201 mm external
product weight	0.87 kg

Offer Sustainability

Sustainable offer status	Not Green Premium product

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.