



Main

Range	EasyLogic
Device short name	PM2K2AIAO
Product or component type	I/O module
Device application	Optional expansion module
Range compatibility	EasyLogic EasyLogic PM2100 PM2130 EasyLogic EasyLogic PM2200 PM2230

Complementary

[Ui] rated insulation voltage	2500 V
Number of outputs	2 analog, 4...20 mA
Output voltage	12 V AC
Analogue input type	Analog input <= 300 Ohm
Number of inputs	2 analog, 4...20 mA
Input voltage	12...30 V AC
Analogue output type	Analog output <= 600 Ohm
Width	90.5 mm
Depth	14.6 mm
Height	53 mm
Product weight	50 g

Environment

ambient air temperature for operation	-10...60 °C
ambient air temperature for storage	-25...70 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1601 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.