

## METSEPM5RD

Power Logic PM5000 - 5RD Remote display 96 x 96 mm monochrome



### Main

Range	PowerLogic
Product or component type	Remote display
Device application	Human-machine dialogue application
Range compatibility	Powerlogic PowerLogic PM5000
Display type	Backlit LCD

### Complementary

Display colour	Monochrome
Display resolution	128 x 128 pixels
Display size	67 x 62.5 mm
Information displayed	Current Frequency Harmonic distortion Voltage Power Energy consumption
Messages display capacity	Graphic objects ( bargraph, button, light...) 6 lines
Local signalling	Communication : green LED Programming indication : amber LED
Control type	4 x push-button
Connector type	RJ45
Mounting mode	Flush-mounted
Mounting support	Remote display on framework
Width	96 mm
Height	96 mm
Embedding depth	21 mm
Projecting depth	27 mm

### Environment

IP degree of protection	IP52 according to IEC 60529
relative humidity	5...95 % at 37 °C
operating altitude	0...3000 m
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1340 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.