

## 3043HSUSB-VW

Clipsal Iconic - USB Charger - 3 sockets - complete product - vivid white



### Main

Range	Clipsal Iconic
Product or component type	USB charger
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	3xUSB 2.0 type A 5 V DC, maximum load current: 2.1 A
Output current	4.5 A

### Complementary

Device mounting	Flush
Device presentation	Complete product
Colour tint	Vivid white
Surface finish	Matt Textured
Fixing mode	By screws
Type of packing	Polybag
Sale per indivisible quantity	1
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-5...50 °C
Relative humidity	15...95 %
Protection type	Short time short-circuit protection
Number of terminals	3 screw terminal
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	4 x 2.5 mm <sup>2</sup> (stranded) 4 x 2.5 mm <sup>2</sup> (flexible) 4 x 2.5 mm <sup>2</sup> (rigid)
Wire stripping length	16 mm
Height	78 mm
Width	120 mm
Depth	36 mm
Embedding depth	35 mm

### Environment

product certifications	RCM
electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP21

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.