



Main

Range	ARGUS
Product or component type	Presence detector with IR receiver
Load type	LED lighting : : 100 W Compact fluorescent lamp : : 100 W Motor : : 100 W Relay : : 5 A - 250 V Halogen lamp : : 1000 W - 230 V Incandescent lamps : : 2000 W - 230 V Fluorescent tube : 900 VA
Colour tint	White

Complementary

Network frequency	50/60 Hz
Input function	Switch External trigger
Output voltage	220...250 V
Output current	10 A
Number of channels	2
Control type	Movement sensor
Function available	Switching, toggling, dimming
Light intensity adjustment	10...2000 lux
Horizontal detection angle	360 °
Detection face	Radius 14000 mm
Device mounting	Flush Surface
Mounting height	2.5 m

Environment

IP degree of protection	IP40 IP52
-------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1611 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.