DOWNLIGHTS

TAYLOR LED CCT4 SELECTABLE











CONSTRUCTION:

- PA66 Nylon coated Aluminium housing
- Polycarbonate trim & Opal diffuser
- · Steel spring clips

FEATURES:

- LED replacement for 50W halogen downlight & 100W GLS
- Integrated driver prewired with 0.6m of flex
- · White trim included
- A range of black, silver, brushed chrome & Matte White trims available
- · High efficacy of 82-113lm/W
- Switch on the back of the fitting allowing selection between 3000K, 4000K, 5000K or 6500K colour temperature







90

108

136





62

65

70















RATED HOURS

LUMENS

IP RATING

Diameter Cut Out Depth

72

92

125


VOLTAGE

ACCESSORIES

RC7TRIM-04	72mm cut out, Black		
RC9TRIM-04	92mm cut out, Black		
RC10TRIM-04	125mm cut out, Black		
RC9TRIM-11	92mm cut out, Matte White		
RC7TRIM-13	72mm cut out, Brushed Chrome		
RC9TRIM-13	92mm cut out, Brushed Chrome		
RC10TRIM-13	125mm cut out, Brushed Chrome		
RC7TRIM-15	72mm cut out, Silver		
RC9TRIM-15	92mm cut out, Silver		
RC10TRIM-15	125mm cut out, Silver		
RC10160TRIM-01	Extension trim for the RC10 from 125mm to 160mm		
RLA350DTR-01	LOADPRO 350W LED Rotary dimmer		
RLA350DTT-01	LOADPRO Touch Dimmer 250W		



DIMENSIONS(mm)





Scan here for more product information



DOWNLIGHTS

TAYLOR LED CCT4 SELECTABLE



	RC7WDL72CCT4-01	RC9WDLCCT4-01	RC10WDLCCT4-01
Comparable to:	50W Halogen	50W Halogen	100W GLS
Total Power (W):	7.3/7.1/7.1/7.2	7.3/7.1/7.2/7.3	10.1/9.5/9.7/9.8
Total Light Output (lm):	590/660/640/590	650/745/745/690	1,020/1,070/1,060/1,020
Efficacy (lm/cctW):	82/94/91/82	90/105/103/95	102/113/110/104
Lux at 1m (lux):	250/280/270/250	290/340/340/320	430/460/450/430
CCT (K):	3000/4000/5000/6500	3000/4000/5000/6500	3000/4000/5000/6500
CRI:	80	80	80
Power Factor (PF):	0.85	0.8	0.9
Weight (kg):	0.21	0.28	0.31

Note: Multiple CCT data shown in format

Warm White / Neutral White / Cool White / Daylight White



ROBUS.COM.AU 67