

Maxi Master Gen II LED Floodlight

MML50S

- Weather protection IP65
- Diecast aluminium body powder coated black
- Lightweight for easy installation



Performance

System Power	50W
Exit Lumen	5250lm
Efficacy	105lm/W
CCT	4000K
CRI	80
Operating Temperature	0°C to 40°C
MacAdam Steps	7SDCM
Ingress Protection Rating	IP65
Impact Rating	IK08
Beam Distribution	Symmetric
Beam Angle	120°
Warranty	5 Years
Lifetime	50,000hrs (L70/B50)


Physical

Dimensions	L200 x W280 x H54mm
Diffuser	Glass Borosilcate
Luminaire Colour	Black
Weight	2kg
Luminaire Material	Aluminium (Die Cast)
Heatsink	Aluminium (Die Cast)
Finish	Powder Coated
Installation	Trunnion

Electrical

Dimming	Non - Dimmable
Voltage	240V
Electrical Rating	Class 1

Line Drawings



Product Images




Accessories

MML50WG	MML50 WIRE GUARD STAINLESS STEEL POWDERCOATED BLACK
MML100WG	MML100 WIRE GUARD STAINLESS STEEL POWDERCOATED BLACK
MML200WG	MML200 WIRE GUARD STAINLESS STEEL POWDERCOATED BLACK
MML300WG	MML300 WIRE GUARD STAINLESS STEEL POWDERCOATED BLACK


Line Drawings

MML Master LED Flood GEN II Transition Mounting Details.


1. 50W (200W) Mounting Detail :



2. 100W Mounting Detail :



3. 200W Mounting Detail :



PIR/027