

Catalogue No: **1606-XLB120E**

POWER SUPPLY 1PH 85-132V AC/170-264V AC TO 24-28V DC 120W 5A

Power Distribution and Protection > Power Supplies and Transformers > Switched Mode Power Supplies > Allen-Bradley Switched Mode Power Supplies > 1606-XL Basic Series, 1-Phase Input



- Efficient power supplies which minimise heat output and reduce associated running costs
- Redundancy module options allow for backup power in critical applications
- The compact footprint maximises usable space with the panel

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Input Voltage, AC, Min	85 V AC min
Input Voltage, AC, Max	264 V AC max
In, Nominal Current, 120V AC	1.7 A
In, Nominal Current, 230V AC	1.04 A
Current, Inrush @100V AC, Max	23 A@100V AC
Current, Inrush @120V AC, Max	27 A@120V AC
Current, Inrush @230V AC, Max	40 A@230V AC
Power Factor	0.54
Indicator Type	LED
Output Voltage, DC, Min	24 V DC min
Output Voltage, DC, Max	28 V DC max
Output Current, 24V DC	5 A @24V DC
Output Current, 28V DC	4.3 A @28V DC
Pout, Real, Rated W	120 W
Height	124 mm
Width	39 mm
Depth	124 mm
Standards Compliance	UL 508 IEC 60950 EN 60950 EN 50178
Certifications	CE

Catalogue No: **1606-XLB120E**

POWER SUPPLY 1PH 85-132V AC/170-264V AC TO 24-28V DC 120W 5A

Power Distribution and Protection > Power Supplies and Transformers > Switched Mode Power Supplies > Allen-Bradley Switched Mode Power Supplies > 1606-XL Basic Series, 1-Phase Input



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -