



THREE CIRCUIT TRACK - STR4890

Universal track - three circuit

Application

Designed for creative retail or residential applications

Design Specifications

- Extruded aluminium profile
- Power coat finish in black or white
- Profile length choices 1m or 2m
- Complete with one end cap and a live end
- Rating: TOTAL current capacity 16A per system.
- Maximum (mass) load limit per track adaptor is 2kg



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Body Colour	Dim (mm)
	STR4890/1WH	240	White	1000(L)
	STR4890/1BK	240	Black	1000(L)
	STR4890/2WH	240	White	2000(L)
	STR4890/2BK	240	Black	2000(L)
	STR4891WH	240	White	
	STR4891BK	240	Black	
	STR4892WH	240	White	

Product	Model No.	Input Voltage (V/AC)	Body Colour	Dim (mm)
	STR4892BK	240	Black	
	STR4893WH	240	White	
	STR4893BK	240	Black	
	STR4894WH	240	White	
	STR4894 BK	240	Black	
	STR4895 WH	240	White	
	STR4895 BK	240	Black	
	STR4896WH	240	White	
	STR4896BK	240	Black	
	STR4897WH	240	White	
	STR4897BK	240	Black	
	STR4898WH	240	White	
	STR4898BK	240	Black	
	STR4899/1 WH		White	
	STR4899/1 BK		Black	

Product	Model No.	Input Voltage (V/AC)	Body Colour	Dim (mm)
	STR4899/2 WH (with 6mm/1M ROD)		White	1000(L)
	STR4899/2 BK (with 6mm/1M ROD)		Black	1000(L)
	STR4899/3 WH (with 1.5mm/1M WIRE)		White	1500(L)
	STR4899/3 BK (with 1.5mm/1M WIRE)		Black	1500(L)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

THREE CIRCUIT TRACK STR4890

Universal track - three circuit

Application

Designed for creative retail or residential applications

Design Specifications

- Extruded aluminium profile
- Powder coat finish in black or white
- Profile length choices 1m or 2m
- Complete with one end cap
- Rating: TOTAL current capacity 16A per system

Track Components

Mini Joiner

Product No.	Colour
STR4891 WH	White
STR4891 BK	Black

Live End

Product No.	Colour
STR4892 WH	White
STR4892 BK	Black

Straight Connector

Product No.	Colour
STR4893 WH	White
STR4893 BK	Black

L-shaped Connector

Product No.	Colour
STR4894 WH	White
STR4894 BK	Black

T-shaped Connector

Product No.	Colour
STR4895 WH	White
STR4895 BK	Black

Cross Shaped Connector

Product No.	Colour
STR4896 WH	White
STR4896 BK	Black



Dimensions



Adjustable Connector

Product No.	Colour
STR4897 WH	White
STR4897 BK	Black

Circuit Adapter

Product No.	Colour
STR4898 WH	White
STR4898 BK	Black

T-bar Mounting Kit

Product No.	Colour
STR4899 WH	White
STR4899 BK	Black

Suspension Unit with Rod

Product No.	Colour
STR48910 WH	White
STR48910 BK	Black

Suspension Unit with Wire

Product No.	Colour
STR48911 WH	White
STR48911 BK	Black

THREE CIRCUIT TRACK

Assembly note: The Track system is designed with a raised spline that runs along one side of the track and the track components all have an arrow on one side. To assemble, insert each component into the track so that the arrow is on the same side as the raised spline.

