

PRODUCT DATASHEET

LVED VAL 40/230...240/PRIM

CV Power supplies 12 V – Non dimmable | CV Power supplies 12 V

AREAS OF APPLICATION

- Suitable for luminaires of protection class II
- For use with low voltage halogen lamps (10...40 W)
- Hotels
- Shop lighting
- Residential interiors

PRODUCT BENEFITS

- Compact housing
- Easy to install and use
- Efficient and reliable

PRODUCT FEATURES

- Short-circuit, overload and overtemperature protection
- Lifetime: up to 30,000 h

TECHNICAL DATA

Electrical data

Nominal voltage	230...240 V
Mains frequency	50/60 Hz
Nominal output voltage	11.4 V
Nominal output power	10...40 W

Dimensions & weight

Length	132.7 mm
Width	31.8 mm
Height	28.1 mm
Product weight	165.00 g

Colors & materials

Casing material	Plastic
-----------------	---------

Temperatures & operating conditions

Ambient temperature range	0...+45 °C
Maximum temperature at tc test point	70 °C
Max.housing temperature in case of fault	110 °C

Lifespan

ECG lifetime	30000 h
--------------	---------

Capabilities

Dimmable	No
Overheating protection	Yes
Overload protection	Yes
Short-circuit protection	Yes

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075030107	LVED VAL 40/230...240/PRIM	Shipping carton box 20	340 mm x 245 mm x 177 mm	14.74 dm ³	3726.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.