

Product data sheet

Characteristics

CLITPDL2K4

Clipsal - LED downlight - 9W - 4000K - IP44 - white trim



Main

Range	Clipsal
Product or component type	Downlight
Device application	Lighting
Market segment	Residential Small commercial

Complementary

Device mounting	Recessed ceiling
Shape	Round
Type of installation	Indoor
Rated power in W	9 W
Light source	LED
Total system power	240 V AC 50 Hz
Luminous flux	950 lm 4000 K warm white
Colour rendering index	R _a =80
Bulb lifespan	50000 h
Beam angle	90 °
Load type	Dimmable LED
Device composition	Plastic integral dimming driver Flex Plug Round white plastic fixed trim Light diffuser soft glow
Trim width	115 mm
Cut-out dimensions	90 mm
Mounting depth	61 mm

Environment

IP degree of protection	IP44
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 % non-condensing

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed
-------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.