




Platinum Exit LED Quickfit Nexus LED Exit LiFePO4 Frame Only

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Exit
Testing System		Nexus LX
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		3.2 W
Mounting		Surface - Universal
Viewing Distance		24 meters
LED Life		100,000 hours
Photometric Classification		C0:D3.2 C90:D3.2
Battery Type		LiFePO4
Height		214 mm
Width		72 mm
Depth		379 mm
Base Colour		White
Battery Replacement		0301302P
IP Rating		IP20
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **PQFNXSLEDPFR**

PLATINUM EXIT LED QUICKFIT NEXUS LED EXIT LIFEPO4 FRAME ONLY

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -