Technical data sheet

Exit LED Quickfit® Platinum exit LED Quickfit Nexus®

p-Range



Range

Platinum range

Product group

Exit LED Quickfit®

Features

- 5 year warranty
- LED technology 100,000 hours plus lamp life
- Low power consumption and LED light source for reduced operation and maintenance costs
- Advance charging technology combined with Lithium iron phosphate battery for long life and low maintenance
- Nexus® monitored, either cabled or wireless
- Quickfit® unique steel slide connect bracket for quick installation and easy maintenance
- Includes all pictograph diffuser options for single or double sided installation
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Retrofit capability; fits into any existing Quickfit mounting bracket
- Frame only available for upgrade of installed product (less mounting bracket and diffusers) - will accept existing diffusers
















Nexus products

Catalogue no.	Description
PQFNXSLEDP	LED platinum Quickfit Nexus LX pictograph exit
PQFNRFLEDP	LED platinum Quickfit Nexus RF pictograph exit

Accessories

Catalogue no.	Description
MQFCL	Cantilever bracket
QFWGCM	Wire guard - ceiling
QFWGWM	Wire guard - wall

Spare parts

Catalogue no.	Description
03-01302P	Battery LiFePO4 3.2V 3.2Ah
PQFNXSLEDP-LB	LED platinum Quickfit Nexus LX pictograph exit less bracket
PQFNRFLEDP-LB	LED platinum Quickfit Nexus RF pictograph exit less bracket
PQFNXSLEDP-FR	LED platinum Quickfit Nexus LX exit frame only
PQFNRFLEDP-FR	LED platinum Quickfit Nexus RF exit frame only

Dimensions

Length	Width	Height (incl. bracket)
379mm	72mm	214mm

Weight

Model	Weight
Nexus LX/RF	1.8kg

Construction

Part	Construction
Body	UV/FR ABS body
Diffuser	Opal acrylic
Bracket	White powder coated zinc steel

Light source

Model	Light source
Nexus LX/RF	Multiple LED 1.6W

Power consumption

Model	Power consumption
Nexus LX/RF	3.2W

Note: Preliminary results





KK106713A9554 - Nov 2017

Photometrics

Model	Class	Classification
Nexus LX/RF	Co	D3.2
	C90	D3.2

Note: Preliminary results

Note: Designed to comply with AS2293 and meet relevant Australian EMC standards

For more information please contact:

ABB Australia Pty Limited

Phone: 1800 60 20 20

E-mail: AU-ABB-Stanilite@abb.com

www.stanilite.com.au

Note: We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilisation of its contents – in whole or in parts – is forbidden without prior written consent of ABB.

Copyright © 2017 ABB All rights reserved



