## Catalogue No: 42EF-R2MPB-F4

## TB RCVR 24VDC VISIBLE RED 20M DO/LO PNP IO-LINK DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Photoelectric Sensors > Allen-Bradley Photoelectric Sensors > Transmitted Beam Sensors > Compact Rectangular





TB RCVR 24VDC VISIBLE RED 20M DO/LO PNP IO-LINK DC-MICRO-4

- Comprehensive range of photoelectric sensing technologies available which include retroreflective, through-beam, diffuse, background suppression, clear object detection, colour detection and fibre-optics
- Extensive range of photoelectric sensors with laser light source available suitable for high precisions applications
- Extensive range of housing styles and mounting options
- Specialised versions with IP69k rating available for high-pressure washdown applications in the food and beverage industry
- Specialised long-range laser sensors available for distance measurement applications
- Specialised versions available with IO-Link technology. This technology enables the data delivery from the sensor directly into a control system in a very efficient manner

Representative Photo Only

(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	42EF RightSight
Component Type Field Switching & Sensing	Photoelectric Sensor
Sensing Mode	Through-Beam Receiver
Light source type	LED
Illumination Mode	Continuous
Colour, light source	Infrared (880nm)
Material, Lens	PMMA / Acrylic / Perspex / Plexiglas (Polymethyl methacrylate)
Shape	Rectangular
Orientation	Straight Through / Right Angle
Mounting (Multiple)	Panel Mount Threaded Nose Threaded Base Mounting Bracket (Ordered Separately)
Thread Size	M18 x 1 size
Teach Mode / Sensitivity Adjustment	N / A sensitivity
Operating Range(s)	10.8 30V DC
Ue, Rated Operational Voltage, DC, min	10.8 V DC
Ue, Rated Operational Voltage, DC, max	30 V DC
Switching Mode	Light or Dark Operate Selectable
Output Type	PNP
Load Current	0.1 A
Connection / Termination	M12 x 1, DC Micro, 4-pin
Number of Conductors	4 qty
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	70 °C max
Humidity Type	Non-condensing
IP Rating	IP67 IP69K



## Catalogue No: 42EF-R2MPB-F4

## TB RCVR 24VDC VISIBLE RED 20M DO/LO PNP IO-LINK DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Photoelectric Sensors > Allen-Bradley Photoelectric Sensors > Transmitted Beam Sensors > Compact Rectangular



