## Catalogue No: **PEJLLXCM1**

## PLATINUM EXIT LED JUMBO NEXUS LX C/MNT S/SIDED PICTO

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit LX





Platinum Exit LED Jumbo Nexus LX Ceiling Mount Single Sided Picto

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
of Edit Ida Hollo	
Component Type Emergency Lighting	Exit
Testing System	Nexus LX
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	9.0 W
Mounting	Surface - Universal
Viewing Distance	36 meters
LED Life	100,000 hours
Photometric Classification	C0:D32 C90:D10
Battery Type	LiFePO4
Height	310 mm
Width	123 mm
Depth	615 mm
Base Colour	White
Diffuser Colour	White on Green
Battery Replacement	0301307P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



## Catalogue No: **PEJLLXCM1**

## PLATINUM EXIT LED JUMBO NEXUS LX C/MNT S/SIDED PICTO

 $Stanilite\ Emergency\ and\ Exit\ Lighting > Platinum > Monitored\ Platinum > Platinum\ Exit\ LX$ 



REFERENCES	
IECEx Certificate	
Supplier Declaration of Conformity:	eJumbo LED Exit Sign, LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Exit LED Jumbo Standard, Nexus LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Exit LED Jumbo Nexus Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-

