



Platinum Exit LED Jumbo Weather Proof Nexus RF Picto

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Exit
Testing System		Nexus RF Infinity
Operating Mode		Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		9.0 W
Mounting		Surface - Universal
Viewing Distance		40 meters
LED Life		100,000 hours
Photometric Classification		C0:D6.3 C90:C2
Battery Type		LiFePO4
Height		280 mm
Width		130 mm
Depth		558 mm
Base Colour		White
Diffuser Colour		White on Green
Battery Replacement		0301307P
IP Rating		IP20
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **PEJLWRF1**

PLATINUM EXIT LED JUMBO WEATHER PROOF NEXUS RF PICTO

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit RF



REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

[Weatherproof Jumbo LED Exit Sign, LifePO4 Battery_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

-

User Manual:

-

Manufacturer Datasheet:

[Platinum Exit LED Jumbo Weatherproof Nexus_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection:

-