Catalogue No: **PEJLWRF3**

PLATINUM EXIT LED JUMBO WEATHER PROOF NEXUS RF PICTO R

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit RF





Platinum Exit LED Jumbo Weather Proof Nexus RF Picto R

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Exit
Testing System	Nexus RF Infinity
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	9.0 W
Mounting	Surface - Universal
Viewing Distance	40 meters
LED Life	100,000 hours
Photometric Classification	C0:D6.3 C90:C2
Battery Type	LiFePO4
Height	280 mm
Width	130 mm
Depth	558 mm
Base Colour	White
Diffuser Colour	White on Green
Battery Replacement	0301307P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



Catalogue No: **PEJLWRF3**

PLATINUM EXIT LED JUMBO WEATHER PROOF NEXUS RF PICTO R

Stanilite Emergency and Exit Lighting > Platinum > Monitored Platinum > Platinum Exit RF



REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	Weatherproof Jumbo LED Exit Sign, LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	Platinum Exit LED Jumbo Weatherproof Nexus_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-

