


AIR CONDITIONING

SRK50ZSA-W / DXK18ZSA-W, 5.0KW



KEY FEATURES

- Modern and stylish design
- 3D Auto airflow for effective and even air distribution
- Allergen clear system to capture and eliminate allergens
- Energy efficient R32 refrigerant
- Optional Wi-Fi control

Indoor			SRK50ZSA-W
Outdoor			SRC50ZSA-W
Power supply			1 Phase 220~240V 50Hz
Capacity	Cooling T1	kW	5.0 (1.2~5.5)
	Heating H1		5.8 (1.2~6.6)
Input	Cooling T1	kW	1.39 (0.27-1.86)
	Heating H1		1.49 (0.26-1.97)
Max running current		A	14.5
Energy label	Cooling T1	Stars	2.5
	Heating H1		3
EER	Cooling T1		3.60
COP	Heating H1		3.89
Sound power level (JIS C9612)	Cooling(Outdoor)	dB(A)	61
	Heating(Outdoor)		63
Sound pressure level (JIS C9612)	Cooling(Indoor)	dB(A)	43-36-28-22
	Heating(Indoor)		47-39-32-24
Silent mode sound pressure level	Cooling(Outdoor)	dB(A)	43
	Heating(Outdoor)		45
Airflow	Cooling(Indoor)	l/s	213-175-113-93
	Heating(Indoor)		253-198-152-113
External dimensions (HXWXD)	Indoor	mm	290x870x230
	Outdoor		640x800(+71)x290
Net weight	Indoor	kg	10
	Outdoor		43.5
Refrigerant piping	Liquid line	mm	Ø6.35
	Gas line		Ø12.7
	Connection method		
Refrigerant R32	Quantity	kg	1.05
	Pre charged to pipe length	m	15
Clean filter			Allergen Clear & Photocatalytic Washable Deodorizing Filter