



Main

Range of product	Modicon Quantum automation platform
Product or component type	Dc discrete output module
Discrete output number	32

Complementary

Group of channels	4 groups of 8
Discrete output logic	Positive logic (source)
Addressing requirement	2 output words
Discrete output voltage	24 V DC 24 V DC
Output voltage limits	19.2...30 V
Absolute maximum output	56 V for 1.3 s decaying pulse 56 V for 1.3 s decaying pulse
Voltage drop	0.4 V 0.5 A 0.4 V 0.5 A
Maximum load current	16 A per module 16 A per module 4 A per group 4 A per group
Surge current	<= 5 A for 0.0005 s <= 5 A for 0.0005 s
Response time	<= 1 ms at state 0 to state 1 <= 1 ms at state 0 to state 1 <= 1 ms at state 1 to state 0 <= 1 ms at state 1 to state 0
Leakage current	0.4 mA 30 V 0.4 mA 30 V
Load inductance	Inductance(H) = 0.5/((current(A)) ² x (switching frequency(Hz))) 50 Hz Inductance(H) = 0.5/((current(A)) ² x (switching frequency(Hz))) 50 Hz
Fault indication	Blown fuse Loss of field power
Associated fuse rating	3 A each point 3 A each point 5 A per group 5 A per group
Isolation between channels and bus	1780 Vrms DC for 1 minute 1780 Vrms DC for 1 minute
Isolation between group	500 Vrms DC for 1 minute 500 Vrms DC for 1 minute
Protection type	Internal output protection by 5 A fuse per group
Power dissipation	1.75 W + (0.4 V x total module load current)
Marking	CE
Local signalling	1 LED green bus communication is present (Active) 1 LED green bus communication is present (Active) 1 LED red external fault detected (F) 1 LED red external fault detected (F) 32 LEDs green input status

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

	32 LEDs green input status
Bus current requirement	330 mA 330 mA
Module format	Standard
Product weight	0.45 kg

Environment


product certifications	ABS BV C-Tick DNV FM Class 1 Division 2 GL GOST RINA RMRS Safety certification non interfering
standards	CSA C22.2 No 142 UL 508
resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
resistance to electromagnetic fields	10 V/m 80...2000 MHz conforming to IEC 801-3 10 V/m 80...2000 MHz conforming to IEC 801-3
ambient air temperature for operation	0...60 °C
ambient air temperature for storage	-40...85 °C
relative humidity	95 % without condensation 95 % without condensation
operating altitude	<= 5000 m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0848 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots

24 Vdc Discrete Output Source Module

Wiring Diagram

