170ENT11001

Modicon Momentum - Ethernet communication adaptor - 10/100 Mbit/s



Main

Range of product	Modicon Momentum automation platform
Product or component type	Ethernet TCP/IP communication adaptor
Communication port protocol	Ethernet TCP/IP
Method of access	Master/slave Peer to peer
Transmission rate	10/100 Mbit/s
Transmission support medium	Shielded twisted pairs cable

Complementary

Module configuration	BOOTP server to assign IP parameters	_
Topology	Multidrop, star network	
Port Ethernet	100BASE-TX	_
Number of devices per segment	032	
Cable distance between devices	1000 m without repeater	
Addressing	IP address user assigned Unique IEEE global address	
Fail state	Fail safe	
Control parameter	CRC-32	
Supply	From I/O base	
Marking	CE	
Local signalling	1 LED green Ethernet network 10 Mbits/s (10T) 1 LED green Ethernet network state (ST) 1 LED green module active (RUN) 1 LED yellow Ethernet network 10 Mbits/s (100T)	
Electrical connection	1 connector RJ45 for 100BASE-TX	
Product weight	0.07 kg	

Environment

LITTIONICITE		
product certifications	CSA UL	
standards	CSA	
IP degree of protection	IP20	
protective treatment	TC	
resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2	
resistance to electromagnetic fields	10 V/m 801000 MHz IEC 801-3	
ambient air temperature for operation	060 °C	
ambient air temperature for storage	-4085 °C	
relative humidity	95 % without condensation	
operating altitude	<= 5000 m	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0925 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold