33036

voltage release MX or XF COM - 200..250 V AC/DC



Main

| Range of product | Masterpact NT Masterpact NW |
|------------------------------|--|
| Range | Masterpact |
| Device short name | MX com |
| Product or component type | Voltage release |
| Device application | Control |
| Range compatibility | Masterpact Masterpact NT circuit breaker Masterpact Masterpact NW circuit breaker |
| [Uc] control circuit voltage | 200/250 V DC 200/250 V AC 50/60 Hz |

Complementary

| Control type | Communicating |
|------------------------------------|--|
| Threshold tripping voltage | 0.71.1 x Un |
| Supply holding power | 4.5 VA |
| Response time | 50 ms |
| Accessory / separate part category | Spare parts Masterpact NT Spare parts Masterpact NW |

Environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or fitnese products for specific user applications. It is the ducty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.