

Product data sheet

Characteristics

47887

Indication contacts, MasterPact NW08 to NW63, additional block, 4 ON/OFF contacts



Main

Product or component type	Auxiliary contact
Device short name	4 OF
Range compatibility	Masterpact MasterPact NW EasyPact EasyPact MVS EasyPact EasyPact EXE
Signal contacts composition	4 NO/NC

Complementary

Auxiliary contacts type	Standard Low level
Breaking capacity (A)	AC-12: 10 A at 240/380 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 10 A at 480 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 6 A at 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 DC-12: 10 A at 24/48 V DC conforming to EN/IEC 60947-2 DC-12: 10 A at 125 V DC conforming to EN/IEC 60947-2 DC-12: 3 A at 250 V DC 50/60 Hz conforming to EN/IEC 60947-2 8 A at 480 V AC 50/60 Hz conforming to UL 489 AC-12: 6 A at 600 V AC 50/60 Hz conforming to UL 489 6 A at 250 V DC conforming to UL 489
Minimum load	100 mA at 24 V 2 mA at 15 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.1 cm
Package 1 Width	4.6 cm
Package 1 Length	6.8 cm
Package 1 Weight	87 g

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Operations and descriptions

Operation	600
Duration of operation	4 min
Operation Description	Assembly and test

Contractual warranty

Warranty

18 months
