



### Main

Range	M400 Series Actuators
Product or component type	Electroc mechanical actuator
Device short name	M400
Product destination	Globe valve

### Complementary

Duty cycle	20 % full load 80 % half load
Material	Aluminium
Enclosure material	ABS/PC
Colour	Aluminium Grey
Transformer rated power in VA	30 VA
Operating force	400 N modulating 60 s 9...25 mm 400 N modulating 60 s 25...32 mm
[Us] rated supply voltage	24 V DC with variation +/- 10 % 24 V AC with variation +/- 25 %, 50...60 Hz
Analogue input range	Selectable Input 0...10 V with <= 100000 Ohm Selectable Input 2...10 V with <= 100000 Ohm Selectable Input 0...5 V with <= 100000 Ohm Selectable Input 5...10 V with <= 100000 Ohm Selectable Input 2...6 V with <= 100000 Ohm Selectable Input 6...10 V with <= 100000 Ohm
Input type	Digital type 5 mA @ 24 V in 20 ms
Power consumption in VA	7 VA
Output voltage	16 V DC with variation +/- 0.3 V
Maximum load current	25 mA
Protection type	Short-circuit
Acoustic level	< 38 dBA
Mechanical robustness	Vibrations - conforming to IEC 68-2-6
Standards	EN 61326 certified 2006 IEC 68-2-2 IEC 68-2-1
Product weight	1.8 kg

### Environment

ambient air temperature for storage	-10...50 °C
ambient air temperature for operation	-10...50 °C
relative humidity	0...90 % - conforming to IEC 68-2-3
IP degree of protection	IP54

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1730 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.