

A9C15032

impulse relay iTL+ - 1P+N - 1NO - 16A - coil 230
VAC 50Hz



Main

Range	Acti 9
Product name	Acti 9 iTL+
Product or component type	Impulse relay
Device short name	iTL+
Device application	Standard
Poles description	1P
Neutral position	Left
Pole contact composition	1 NO
[In] rated current	16 A
Network type	AC
[Uc] control circuit voltage	230 V AC 50 Hz

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	230 V AC 50 Hz
Control type	Remote and manual control
Control signal type	Impulse
Switching frequency	6 switching operation/minute
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 5 mA
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Product weight	70 g
Electrical durability	AC-21 : 5000000 cycles AC-22 : 5000000 cycles
Connections - terminals	Tunnel type terminals top or bottom 2 cable(s) 1.5 mm ² rigid Tunnel type terminals top or bottom 2 cable(s) 1.5 mm ² flexible with ferrule Tunnel type terminals top or bottom 2 cable(s) 2.5 mm ² rigid Tunnel type terminals top or bottom 2 cable(s) 2.5 mm ² flexible without cable end Tunnel type terminals top or bottom 1 cable(s) 4 mm ² rigid Tunnel type terminals top or bottom 1 cable(s) 4 mm ² flexible without cable end
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	No auxiliary

Environment

standards	EN 669-2-2
quality labels	NF
noise level	30 dB
IP degree of protection	IP20 on opening conforming to IEC 60529 IP40 in enclosure conforming to IEC 60529
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % (55 °C)
ambient air temperature for operation	-5...55 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

ambient air temperature for storage	-40...60 °C
-------------------------------------	-------------

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------
