



Main

Range	Acti 9
Product name	Acti 9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	3P

Complementary

[In] rated current	10 A 16 A 2 A 20 A 25 A 4 A 6 A
Fuse curve	AM GG
Fuse size	10.3 x 38 mm
[Ue] rated operational voltage	500 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	75 mm
Colour	White
Connections - terminals	Screw clamp terminals 1 cable(s) 0.75...10 mm ² rigid Screw clamp terminals 2 cable(s) 0.75...4 mm ² rigid Screw clamp terminals 1 cable(s) 0.5...6 mm ² flexible Screw clamp terminals 2 cable(s) 0.5...6 mm ² flexible
Wire stripping length	12 mm
Tightening torque	2 N.m

Environment

standards	IEC 60269-1/2 IEC EN 60947-3
IP degree of protection	IP20
pollution degree	3
ambient air temperature for operation	-20...60 °C
ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1105 - Schneider Electric declaration of conformity

REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations