



Main

Device short name	OF SD
Product or component type	Auxiliary contact
Range compatibility	PowerPact PowerPact B Compact Compact NSXm
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Mounting mode	Clip-on
[Ith] conventional free air thermal current	5 A
[Ie] rated operational current	Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category AC-12 : 5 A network: AC/DC 50/60 Hz at 24 V Utilisation category AC-12 : 5 A network: AC/DC 50/60 Hz at 48 V Utilisation category AC-12 : 5 A network: AC/DC 50/60 Hz at 110 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 220...240 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 380...440 V Utilisation category AC-15 : 5 A network: AC/DC 50/60 Hz at 24 V Utilisation category AC-15 : 5 A network: AC/DC 50/60 Hz at 48 V Utilisation category AC-15 : 4 A network: AC/DC 50/60 Hz at 110 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 220...240 V Utilisation category AC-15 : 2.5 A network: AC 50/60 Hz at 380...440 V Utilisation category DC-12 : 5 A network: AC/DC 50/60 Hz at 24 V Utilisation category DC-12 : 2.5 A network: AC/DC 50/60 Hz at 48 V Utilisation category DC-12 : 0.6 A network: AC/DC 50/60 Hz at 110 V Utilisation category DC-14 : 2.5 A network: AC/DC 50/60 Hz at 24 V Utilisation category DC-14 : 1.2 A network: AC/DC 50/60 Hz at 48 V Utilisation category DC-14 : 0.35 A network: AC/DC 50/60 Hz at 110 V Utilisation category DC-14 : 0.05 A network: DC at 250 V Utilisation category DC-14 : 1 A network: AC/DC 50/60 Hz at 24 V Utilisation category DC-14 : 0.2 A network: AC/DC 50/60 Hz at 48 V Utilisation category DC-14 : 0.05 A network: AC/DC 50/60 Hz at 110 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 660...690 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 660...690 V
Minimum load	5 mA at 17 V DC
Auxiliary connection terminal	Spring
Wire stripping length	8 mm front
Length	1 mm

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1649 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.