



### Main

Device short name	I/O
Product or component type	I/O module
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600 Compact Compact NSX Masterpact Masterpact NT Masterpact Masterpact NW PowerPact PowerPact H PowerPact PowerPact J PowerPact PowerPact L PowerPact PowerPact P PowerPact PowerPact R Masterpact Masterpact MTZ
Product name	Enerlin'X IO

### Complementary

Communication network type	Universal Logic Plug on 2 RJ45 connectors
[Us] rated supply voltage	24 V DC (- 20...10 %)
Current consumption	165 mA
Electromagnetic compatibility	Surge immunity test : according to EN/IEC 61000-4-5 Surge immunity test : according to EN/IEC 61000-4-5 Electrostatic discharge immunity test : according to EN/IEC 61000-4-2 Immunity to radiated fields : 10 V/m according to EN/IEC 61000-4-3
Number of inputs	6 digital 1 analog
Input type	Digital at state 1 : 19.8...25.2 V - DC - 6.1...8.8 mA Digital at state 0 : 0...19.8 V - DC - 0 mA
Number of outputs	3 digital
Output type	Digital : 250 V - AC - 5 A
Cable length	10 m
Mounting mode	By clips
Mounting support	35 mm DIN rail
Control type	By software
Time delay	0...20 s
Vibration frequency	5...8.4 Hz
Connections - terminals	Screw terminal block
Product certifications	CE CULus FCC GOST
Standards	IEC 60947-6-2 IEC 60950 UL 508 UL 60950
Depth	70.6 mm
Height	116 mm
Width	71.7 mm
Product weight	229.5 g

### Environment

relative humidity	5...85 %
IP degree of protection	IP2x : connectors IP4X : front panel IP3x : other parts
ambient air temperature for operation	-20...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

ambient air temperature for storage	-40...85 °C
pollution degree	3
flame retardance	According to UL V0
shock resistance	1000 m/s <sup>2</sup>

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1409 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available