



Main

Range of product	Easypact CVS400...630
Product or component type	Circuit breaker
Device short name	CVS630F
Device application	Distribution
Poles description	3P
Protected poles description	3d
Earth-leakage protection	Without
[In] rated current	630 A (40 °C)
Breaking capacity code	F
Network type	AC
Breaking capacity	36 kA Icu conforming to IEC 60947-2 at 380/415 V AC 50/60 Hz 30 kA Icu conforming to IEC 60947-2 at 440 V AC 50/60 Hz 40 kA Icu conforming to IEC 60947-2 at 220/240 V AC 50/60 Hz
Utilisation category	Category A
Local signalling	LED 105 % Ir LED 90 % Ir LED ready
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit rating	600 A (40 °C)
Protection type	Overload protection (thermal) Short-circuit protection (magnetic)

Complementary

Network frequency	50/60 Hz
Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connections - terminals	Screw connection
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
Thermal protection adjustment range	0...600 A
[Ics] rated service breaking capacity	40 kA conforming to IEC 60947-2 220/240 V AC 50/60 Hz 36 kA conforming to IEC 60947-2 380/415 V AC 50/60 Hz 23 kA conforming to IEC 60947-2 440 V AC 50/60 Hz
Mechanical durability	15000 cycles
Electrical durability	4000 cycles conforming to IEC 60947-2 415 V In
Connection pitch	45 mm
Contact position indicator	Yes
Long time pick-up adjustment type Ir	Adjustable
Long time pick-up adjustment range	0.7...1 x In
Long time delay adjustment type	Fixed
Short-time delay adjustment type	Fixed
Instantaneous pick-up adjustment type li	Adjustable

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Instantaneous pick-up adjustment range	4...8 x I _n
Height	255 mm
Width	140 mm
Depth	110 mm

Environment

electrical shock protection class	Class II
standards	EN 60947-2 IEC 60947-2
product certifications	GOST IEC
IP degree of protection	IP40
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1041 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available