

M9F11316

Multi 9 - C60N - MCB - 3P - 16 A - C Curve - 415 V - 10 kA



Main

Range	Multi 9
Product name	Multi 9 C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	3P
Number of protected poles	3
[In] rated current	16 A at 50 °C conforming to EN/IEC 60947-2
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	Icu 30 kA at <= 125 V DC conforming to EN/IEC 60947-2 Icu 10 kA at 415 V AC 50/60 Hz between phases conforming to EN/IEC 60947-2 Icu 20 kA at 240 V AC 50/60 Hz between phases conforming to EN/IEC 60947-2 Icu 6 kA at 440 V AC 50/60 Hz between phases conforming to EN/IEC 60947-2
Utilisation category	Category A conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Standards	EN/IEC 60947-2
Product certifications	CCC EAC KC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	<= 125 V DC 240 V between phases AC 50/60 Hz 415 V between phases AC 50/60 Hz 440 V between phases AC 50/60 Hz
Magnetic tripping limit	8.5 x In +/- 20 % AC 12 x In +/- 20 % DC
[Ics] rated service breaking capacity	7.5 kA 75 % x Icu at 415 V AC 50/60 Hz conforming to EN/IEC 60947-2 16 kA 75 % x Icu at 240 V AC 50/60 Hz conforming to EN/IEC 60947-2 4.5 kA 75 % x Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 30 kA 100 % x Icu at <= 125 V DC conforming to EN/IEC 60947-2
Limitation class	3
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Depth	72 mm
Product weight	0.36 kg
Colour	Grey
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminal, top or bottom rigid wire(s) 1...25 mm ² max Tunnel type terminal, top or bottom flexible wire(s) 1...25 mm ² max Tunnel type terminal, top or bottom flexible with ferrule wire(s) 1...25 mm ² max
Wire stripping length	14 mm (top or bottom)
Tightening torque	2 N.m (top or bottom)
Earth-leakage protection	Separate block

Environment

heat dissipation	7.5 W 415 V 16 A
IP degree of protection	IP20 conforming to IEC 60529 IP40 for modular enclosure conforming to IEC 60529
pollution degree	3 conforming to EN/IEC 60947-2
overvoltage category	IV
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % (55 °C)
ambient air temperature for operation	-30...70 °C
ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations