

Main

Range	Spacial
Product or component type	Drive flush mounting kit
Accessory / separate part category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Spacial SF and SM enclosures Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 Altivar variable speed drive ATV340
NEMA size	4
Motor power kW	15 kW 220/240 V 18.5 kW 220/240 V 22 kW 220/240 V 30 kW 380/480 V 37 kW 380/480 V 45 kW 380/480 V
Mounting location	Mode 2 : inside enclosure Mode 1 : back of enclosure on mounting plate
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic. 1 x fan support 1 x cover for fan protection

Complementary

Permanent permissible load	28.7 kg
Colour	Grey RAL 7035
Height	External : 800 mm Cut-out : 735 mm
Width	External : 385 mm Cut-out : 325 mm
Depth	Wall-enclosure separation : 151.5 mm
Product weight	8.102 kg
Services	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold