



### Main

Range	LexCom
Product or component type	19" patchcord guiding panel
Colour tint	Light grey (RAL 7035) Dark grey (RAL 7016)
Provided equipment	2 quick fix 19" mountings
Additional information	4 openable rings

### Complementary

Number of rack unit	1U
Material	DC01 for metal sheet PA66 GF20 for plastic part PC for plastic part
Width	490 mm 1.6 ft
Height	45 mm 0.147 ft
Depth	100 mm 0.328 ft

### Environment

ambient air temperature for operation	-10...55 °C 14...131 °F
standards	IEC 60297 NF C 20-150

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0935 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.