



Main

Range of product	Actassi
Product or component type	19" uprights
Device application	Overhead patching
Number of units 19"	4U - 350 mm
Enclosure mounting	Overhead Tray mounted Cable ladder mounted
Product specific application	To mount 19" equipment
Enclosure type	Open frame
Colour tint	Uprights : raven black

Complementary

Device composition	2 x 19" uprights
Permanent permissible load	Static : 15 kg
Provided equipment	2 x 19" uprights (vertical) 4 x mounting bracket (angled) 4 x bolts and nuts 4 x cord self-lock grip strip 2 x cord manager 1 x label holder
Material	Steel
Surface finish	Epoxy-polyester powder
Width	500 mm
Depth	160 mm

Environment

standards	IEC 60297-3-100 EIA-310D
-----------	-----------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0000 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.