

# Inverter Heat Pump.

# SRK-ZK


Wall mounted type

## Hyper Inverter

PRODUCTS



SRK63ZK-S / SRK71ZK-S



SRK63ZK-S / SRK71ZK-S



The SRK71ZK-S can be selected for use with the SCM Multi system outdoor unit.

**FUNCTIONS**

**Comfortable Air Flow Functions:** Allergen System, Self Clean Operation, Allergen Filter, SUN Filter, Auto Flap, Memory, Air Scroll, UP/DOWN, Lateral Swing.

**Comfortable Functions:** Fuzzy, Auto, HI POWER, 3HOT Keep.

**Convenient & Economy Functions:** Economy, DRY, OFF Timer, Sleep, 24h Timer On/Off, On Timer.

**Maintenance & Prevention Functions:** MC, Self Diagnostic, Detachable.

**Others:** Back-up Switch, Auto Restart, 24h ON, Luminous.

Indoor		SRK63ZK-S	SRK71ZK-S
Outdoor		SRC63ZK-S	SRC71ZK-S
Power Supply		1 Phase 220~240V 50Hz	
Capacity	Cooling T1	6.3 (2.15~7.10)	7.1 (2.15~8.00)
	Heating H1	7.1 (1.7~9.50)	8.0 (1.60~10.00)
	Heating H2	7.70	7.78
Input	Cooling T1	1.76 (0.54~2.30)	2.16 (0.54~2.80)
	Heating H1	1.79 (0.37~3.30)	2.14 (0.37~3.40)
	Heating H2	2.85	2.9
Energy Label	Cooling T1	2	1.5
	Heating H1	3	2.5
Energy Star		Yes	
EER	Cooling T1	3.58	3.29
COP	Heating H1	3.97	3.74
	Heating H2	2.77	2.77
Sound Power Level (JIS C9612)	Cooling (Outdoor)	62	66
	Heating (Outdoor)	63	63
Sound Pressure Level (JIS C9612)	Cooling (Indoor)	47-43-37-26	49-45-39-26
	Heating (Indoor)	44-41-36-33	46-43-38-35
Airflow	Cooling (Indoor)	308	325
	Heating (Indoor)	342	358
External Dimensions (HXWXD)	Indoor	318X1098X248	
	Outdoor	750X880(+88)X340	
Net Weight	Indoor	15	
	Outdoor	57	
Refrigerant Piping	Liquid Line	Ø6.35	
	Gas Line	Ø15.88	
	Connection Method	Flare connection	
Refrigerant R410A	Quantity	1.8	
	Pre Charged To Pipe Length	15	
Clean Filter		Allergen Clear & Photocatalytic Washable Deodorizing Filter	