

# PRODUCT DATASHEET

## ST R63 32 60° 4 W/2700 E27

LED STAR R63 | LED reflector lamps R63 with retrofit screw base



---

### AREAS OF APPLICATION

- Display cabinets and shop windows
- Museums, art galleries
- Hospitality
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Long lifetime of up to 15,000 h
- Low energy consumption
- Easy replacement of halogen lamps thanks to compact design
- Instant 100 % light, no warm-up time

---

### PRODUCT FEATURES

- Professional LED alternative to halogen lamps
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

Rated wattage	4.00 W
Nominal wattage	4.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	32 W
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.40


### Photometrical data

Nominal luminous flux	360 lm
Rated luminous flux	360 lm
Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	360 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>
Color rendering index Ra	$\geq 80$
Nominal useful luminous flux 90°	360 lm
Rated useful luminous flux 90°	360 lm

### Light technical data

Beam angle	60 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Nominal beam angle	60 °
Rated beam angle (half peak value)	60.00 °

Dimensions & weight



<b>Overall length</b>	104.0 mm
<b>Diameter</b>	63.0 mm
<b>Outer bulb</b>	R63
<b>Length</b>	104.0 mm
<b>Maximum diameter</b>	63.0 mm

Temperatures & operating conditions

<b>Maximum temperature at tc test point</b>	48 °C
---	-------

Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000

Additional product data

<b>Base (standard designation)</b>	E27
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Design / version</b>	Clear
<b>Show WEEE picto</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

<b>Dimmable</b>	No
-----------------	----

Certificates & standards

<b>Energy efficiency class</b>	A+
<b>Energy efficiency class</b>	A+
<b>Energy consumption</b>	4 kWh/1000h

## Country-specific categorizations

<b>ILCOS</b>	DRRR-4/827-220-240-E27-63/63
<b>Order reference</b>	LEDSR6332 4W/82

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075055353	ST R63 32 60° 4 W/2700 E27	Shipping carton box 10	333 mm x 141 mm x 136 mm	6.39 dm <sup>3</sup>	538.00 g
4058075808621	ST R63 32 60° 4 W/2700 E27	Shipping carton box 6	410 mm x 154 mm x 134 mm	8.46 dm <sup>3</sup>	452.00 g
4058075817616	ST R63 32 60° 4 W/2700 E27	Shipping carton box 20	332 mm x 252 mm x 122 mm	10.21 dm <sup>3</sup>	1063.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## REFERENCES / LINKS

For further products and actual information concerning LED lamps see

▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.