Catalogue No: PBLWEM46LM

PLATINUM BATTEN LED WEATHER PROOF EM 4600Im MAINTAINED

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Batten EM





Platinum Batten LED Weather Proof EM 4600 lumens Maintained

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Batten
Testing System	Single Point Unit
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	40.5 W
Mounting	Surface - Universal
LED Life	75,000 hours
Lumen Output	4600 lumens
Photometric Classification	C0:D80 C90:D63
Battery Type	LiFePO4
Height	90 mm
Width	140 mm
Depth	1560 mm
Base Colour	Grey
Diffuser Colour	Frosted
Battery Replacement	0301307P
IP Rating	IP65
IK Rating	IK08
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



Catalogue No: PBLWEM46LM

PLATINUM BATTEN LED WEATHER PROOF EM 4600Im MAINTAINED

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Batten EM



REFERENCES	
IECEx Certificate	
Supplier Declaration of Conformity:	Weatherproof LED Battens, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Stanilite Batten LED Weatherproof Standard, Nexus® LX, Nexus RF_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	Platinum Batten LED Weatherproof - 5 Foot_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-

