



# G2 LED Slide Connect Exit Sign

CAT NO. 686200/LI, 686201/LI, 686203/LI, 686204/LI, 686206/LI, 686207/LI, 686208/LI, 686209/LI, 686211/LI, 686212/LI



686200/LI

Mode of operation	Maintained
Supply voltage	230 - 240V a.c. 50Hz
Max power consumption	3W
Battery	Li-ion 6.4V 0.57Ah with PCM - B
IP rating	IP20
Body construction	ABS
Compliance	AS/NZS 2293 AS/NZS60598  

# G2 LED Slide Connect Exit Sign

CAT NO. 686200/LI, 686201/LI, 686203/LI, 686204/LI, 686206/LI, 686207/LI, 686208/LI, 686209/LI, 686211/LI, 686212/LI



686200/LI

- Retrofits to previous generation Minitronics Slide Connect bracket
- One box solution
- Can be wall, ceiling or cantilever mounted
- Large terminal block for ease of connection
- Stand alone and Axiom versions available
- Low cost maintenance
- Available in White, Silver and black body
- iSmart™ temperature sensing technology for the LIION battery
- Electronics designed to lengthen the life of the battery, minimising maintenance costs
- Environmentally friendly battery
- 5 year warranty
- Manufactured in Australia

SPU	
Cat No.	Description
686200/LI	White body c/w running man sheets (set of 4)
686201/LI	White body c/w EXIT sheets, Peel-off-arrow (set of 3)
686208/LI	Silver body c/w Running man sheets (set of 4)
686209/LI	Silver body c/w EXIT sheets, Peel-off-arrow (set of 3)
686206/LI	Black body c/w running man sheets (no downward lens)

Computer Monitored SPU's AXIOM Wireless	
Cat No.	Description
686203/LI	White body c/w running man sheets (set of 4)
686204/LI	White body c/w EXIT sheets, Peel-off-arrow (set of 3)
686211/LI	Silver body c/w running man sheets (set of 4)
686212/LI	Silver body c/w EXIT sheets, Peel-off-arrow (set of 3)
686207/LI	Black body c/w running man sheets (no downward lens)

Accessories	
Cat No.	Description
662001	Battery pack Li-ion 6.4V 0.57Ah with PCM - B
686215	Cantilever bracket, White
686216	Wire suspension kit, 2 x 6m
686235	Wire guard single sided
686236	Wire guard double sided

Classification	Maximum spacing between luminaires						
	Mounting Height (Metres)						
Metres	2.1	2.4	2.7	3	3.3	3.6	4
D3.2	6.5	6.6	6.6	6.5	6.4	6.2	5.8
B3.2	4.1	4.2	4.3	4.4	4.3	4.3	4.1

Classification (all models)	
C0	C90
D3.2	B3.2

Legrand - Australia  
1300 369 777  
www.legrand.com.au  
ABN 31 000 102 661

Legrand - New Zealand  
0800 476 009  
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.