

- Marine grade 316 (non-magnetic) stainless steel construction.
- Polyester Coated
- Unique, stainless steel 'ball bearing' locking mechanism.
- Rounded 'off-set' tip, to speed up insertion.
- Smooth rounded edges, for safe handling.
- Self-locking, for easier and faster installation compared with traditional restraint systems.
- An efficient and effective way of securing cables or other materials in environmentally harsh and corrosive conditions.
- Provides heavy duty and long-lasting cable bundling solution in comparison to nylon cable ties.
- Suited to: Commercial, Industrial, Mining, Marine and Infrastructure installations.



| | |
|----------------------------|-----------------|
| Working Temperature | -40°C to 110°C |
| Minimum Tensile | 1568N (160Kg's) |
| Chemical Resistance | Excellent |
| Flame Retardant | Non Flammable |
| UV Resistance | Excellent |

| Code | Description | Packing | MOQ | Ctn |
|--------------|--------------------------------|----------|-----|-----|
| CCT-150/46SS | S/S Coated Cable Tie 150x4.6mm | 100/Pack | 1 | 50 |
| CCT-200/46SS | S/S Coated Cable Tie 200x4.6mm | 100/Pack | 1 | 50 |
| CCT-260/46SS | S/S Coated Cable Tie 260x4.6mm | 100/Pack | 1 | 50 |
| CCT-290/46SS | S/S Coated Cable Tie 290x4.6mm | 100/Pack | 1 | 40 |
| CCT-360/46SS | S/S Coated Cable Tie 360x4.6mm | 100/Pack | 1 | 25 |
| CCT-520/46SS | S/S Coated Cable Tie 520x4.6mm | 100/Pack | 1 | 20 |
| CCT-680/46SS | S/S Coated Cable Tie 680x4.6mm | 100/Pack | 1 | 15 |
| CCT-840/46SS | S/S Coated Cable Tie 840x4.6mm | 100/Pack | 1 | 15 |
| CCT-200/79SS | S/S Coated Cable Tie 200x7.9mm | 100/Pack | 1 | 25 |
| CCT-290/79SS | S/S Coated Cable Tie 290x7.9mm | 100/Pack | 1 | 25 |
| CCT-360/79SS | S/S Coated Cable Tie 360x7.9mm | 100/Pack | 1 | 20 |
| CCT-520/79SS | S/S Coated Cable Tie 520x7.9mm | 100/Pack | 1 | 10 |
| CCT-680/79SS | S/S Coated Cable Tie 680x7.9mm | 100/Pack | 1 | 10 |
| CCT-840/79SS | S/S Coated Cable Tie 840x7.9mm | 100/Pack | 1 | 10 |