

Hollow wall anchor yellow zinc plated \varnothing 8-13 mm (x 100)

Characteristics

\varnothing : M4
Drilling \varnothing (mm) : 8
Wall thickness (mm) : 8 - 13
Hollow brick tensile load (daN*) : 45
Hollow brick shear load (daN*) : 120
12 mm plasterboard tensile load (daN*) : 20
12 mm plasterboard shear load (daN*) : 40
Quantity : 100

Materials

- Hollow materials
- Plasterboard

Benefits

- Anti-rotation bars.

GENERAL INFORMATION

Technical details

Yellow zinc plated steel.
Phillips® drive.

Application(s)

All metal, light duty, cavity fixing for plasterboard and other hollow wall materials.

LOGISTIC INFORMATION

Packaging



Basic plastic bag

Height (cm) : 7.5
 Length (cm) : 20
 Depth (cm) : 15
 Net weight (kg) : 0.8
 Gross weight (kg) : 0.81



3 700882 169693

Outer package 1



Carton box

Height (cm) : 16
 Length (cm) : 35
 Depth (cm) : 26
 Net weight (kg) : 19.2
 Gross weight (kg) : 19.65



3 700882 141842

x 24.00

Outer package 2



Pallet

Height (cm) : 114
 Length (cm) : 114
 Depth (cm) : 81
 Net weight (kg) : 691.2
 Gross weight (kg) : 727.27



3 700882 143136

x 864.00