

Hollow wall anchor yellow zinc plated \emptyset 0-5 mm (x 100)

Characteristics

\emptyset : **M4**
 Drilling \emptyset (mm): **8**
 Wall thickness (mm): **0-5**
 Hollow brick tensile load (daN*): **30**
 Hollow brick shear load (daN*): **40**
 12 mm plasterboard tensile load (daN*): **20**
 12 mm plasterboard shear load (daN*): **35**
 Quantity: **100**

Materials

- Hollow materials
- Plasterboard

Benefits

- Anti-rotation bars.

GENERAL INFORMATION

■ Technical details

Yellow zinc plated steel.
Phillips® drive.

■ Application(s)

All metal, light duty, cavity fixing for plasterboard and other hollow wall materials.

LOGISTIC INFORMATION

■ Packaging



Basic plastic bag

Height (cm) : 7.5
 Length (cm) : 20
 Depth (cm) : 15
 Net weight (kg) : 0.53
 Gross weight (kg) : 0.53



3 700882 169662

■ Outer package 1



x 30.00

Carton box

Height (cm) : 16
 Length (cm) : 35
 Depth (cm) : 26
 Net weight (kg) : 15.75
 Gross weight (kg) : 16.23



3 700882 141828

■ Outer package 2



x 480.00

Pallet

Height (cm) : 114
 Length (cm) : 114
 Depth (cm) : 81
 Net weight (kg) : 252
 Gross weight (kg) : 279.68



3 700882 143112