

Hollow wall anchor yellow zinc plated \varnothing 10-16 mm (x 50)

Characteristics

\varnothing : **M4**
 Drilling \varnothing (mm): **8**
 Wall thickness (mm): **10 - 16**
 Hollow brick tensile load (daN*): **50**
 Hollow brick shear load (daN*): **120**
 12 mm plasterboard tensile load (daN*): **20**
 12 mm plasterboard shear load (daN*): **40**
 Quantity : **50**

Materials

- Hollow materials
- Plasterboard

Benefits

- Anti-rotation bars.

GENERAL INFORMATION

■ Technical details

Yellow zinc plated steel.
Phillips® drive.

■ Application(s)

All metal, light duty, cavity fixing for plasterboard and other hollow wall materials.

LOGISTIC INFORMATION

■ Packaging



Basic plastic bag

Height (cm) : 7.5
 Length (cm) : 20
 Depth (cm) : 15
 Net weight (kg) : 0.4
 Gross weight (kg) : 0.41



3 700882 169709

■ Outer package 1



Carton box

Height (cm) : 16
 Length (cm) : 35
 Depth (cm) : 26
 Net weight (kg) : 12
 Gross weight (kg) : 12.48



3 700882 141859

■ Outer package 2



Pallet

Height (cm) : 114
 Length (cm) : 114
 Depth (cm) : 81
 Net weight (kg) : 576
 Gross weight (kg) : 619.04



3 700882 143143

x 1440.00