

Hollow wall anchor yellow zinc plated \varnothing 6-10 mm (x 100)

Characteristics

\varnothing : M4
Drilling \varnothing (mm) : 8
Wall thickness (mm) : 6 - 10
Hollow brick tensile load (daN*) : 20
Hollow brick shear load (daN*) : 35
12 mm plasterboard tensile load (daN*) : 20
12 mm plasterboard shear load (daN*) : 40
Quantity : 25

Materials

- Hollow materials
- Plasterboard

Benefits

- Anti-rotation bars.

GENERAL INFORMATION

Technical details

Yellow zinc plated steel.
Phillips® drive.

Application(s)

All metal, light duty, cavity fixing for plasterboard and other hollow wall materials.

LOGISTIC INFORMATION

Packaging



Basic plastic bag

Height (cm) : 7.5
 Length (cm) : 20
 Depth (cm) : 15
 Net weight (kg) : 0.70
 Gross weight (kg) : 0.71



3 700882 169679

Outer package 1



Carton box

Height (cm) : 16
 Length (cm) : 35
 Depth (cm) : 26
 Net weight (kg) : 16.82
 Gross weight (kg) : 17.27

x 24.00



3 700882 141835

Outer package 2



Pallet

Height (cm) : 114
 Length (cm) : 114
 Depth (cm) : 81
 Net weight (kg) : 605.66
 Gross weight (kg) : 641.73



3 700882 143129

x 864.00