

## Director 2 LED Exit Light

### DIRLEDPDSL

- Wall & Ceiling mount, complete with replaceable lithium iron phosphate (LiFeP04) battery
- Manual test and maintained emergency exit
- Also available in DALI version



#### Performance

System Power	5W
Exit Lumen	220lm
Efficacy	48lm/W
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Warranty	3 Years
Lifetime	50,000hrs (L70/B50)

#### Physical

Dimensions	L380 x W160 x H220mm
Diffuser	Acrylic
Luminaire Colour	White
Weight	1kg
Luminaire Material	Plastic (Acrylic)
Driver Location	Integrated
Finish	White
Installation	Ceiling Surface Mounted

#### Emergency

Testing System	Self Test
Battery Capacity	1100mA
Emergency Mode Wattage	5W
Emergency Mode Lumen	48lm
Classification	C0/C180: D10 & C90/C270: D10
Viewing Distance	24m

#### Electrical

Voltage	240V
Electrical Rating	Class 2

#### Accessories

BATPK1500/1L11	LiFePO4, battery pack 1 CELL3.2V 1500mAh
----------------	--

#### AS/NZS 2293.1:2018 Classification Table

ALLOWABLE LUMINAIRE MOUNTING HEIGHT (M)	LUMINAIRE MAXIMUM SPACING FOR EACH PLAN (M)	
	C0/180	C90/C270
2.1	7.8	8.5
2.4	8	8.8
2.7	8.1	8.9

#### Line Drawings

