

Double sided foam tape 12 mm x 10 m



Characteristics

Colour : **White**
 Length (m) : **10**
 Width (mm) : **12**
 Thickness (mm) : **1**

Benefits

- For interior and exterior use (good UV moisture and solvent resistance).
- Excellent shear strength.
- Can be torn by hand.

GENERAL INFORMATION

Description

Double-sided foam tape, solvent-based acrylic adhesive.

Technical details

Adhesion on steel: N/cm: 12.
 Breaking load: N/mm²: 65/10.
 Temperature resistance: -15 to +100 °C.
 Application temperature: 0 to +35 °C.
 Bonding period: 24 h at 23 °C.
 Ideal storage temperature: +10 to +30 °C.

Application(s)

Assembly operations for which good load-bearing capacity is required.
 Fitting mirrors, beading, and mouldings.
 Signs and panels.

LOGISTIC INFORMATION

Packaging



Roll

Height (cm) : 1.2
 Length (cm) : 14
 Depth (cm) : 14
 Net weight (kg) : 0.05
 Gross weight (kg) : 0.05



Outer package 1



Carton box

Height (cm) : 16.8
 Length (cm) : 30
 Depth (cm) : 31
 Net weight (kg) : 2.16
 Gross weight (kg) : 2.66

x 48



Outer package 2



Pallet

Height (cm) : 130
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 120.96
 Gross weight (kg) : 163.96



x 2688