

## Double sided foam tape 24 mm x 10 m



## Characteristics

Colour : **White**  
 Length (m) : **10**  
 Width (mm) : **24**  
 Thickness (mm) : **1**

## Benefits

- For interior and exterior use (good UV moisture and solvent resistance).
- Excellent shear strength.
- Can be torn by hand.

## GENERAL INFORMATION

## Description

Double-sided foam tape, solvent-based acrylic adhesive.

## Technical details

Adhesion on steel: N/cm: 12.  
 Breaking load: N/mm<sup>2</sup>: 65/10.  
 Temperature resistance: -15 to +100 °C.  
 Application temperature: 0 to +35 °C.  
 Bonding period: 24 h at 23 °C.  
 Ideal storage temperature: +10 to +30 °C.

## Application(s)

Assembly operations for which good load-bearing capacity is required.  
 Fitting mirrors, beading, and mouldings.  
 Signs and panels.

## LOGISTIC INFORMATION

## Packaging



## Roll

Height (cm) : 2.4  
 Length (cm) : 14  
 Depth (cm) : 14  
 Net weight (kg) : 0.09  
 Gross weight (kg) : 0.09



## Outer package 1



x 24

## Carton box

Height (cm) : 16.8  
 Length (cm) : 30  
 Depth (cm) : 31  
 Net weight (kg) : 2.04  
 Gross weight (kg) : 2.54



## Outer package 2



x 1344

## Pallet

Height (cm) : 130  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 114.24  
 Gross weight (kg) : 157.24

